

*a*  
We claim  
CLAIMS:

1. A method for imparting (topographical) or protective features to a substrate comprising the steps of:
  - 5 (a) providing a sheet material having a top surface and bottom surface, comprising two or more layers, ~~comprising~~ <sup>including</sup> an upper layer and a lower layer, said upper layer being a microporous ultrahigh molecular weight polyolefin film, and said lower layer comprising a thermosettable melt-flowable composition comprising one or more thermosettable polymers;
  - 10 (b) contacting said bottom surface of said sheet material with said substrate, leaving said top surface of said sheet material exposed;
  - (c) heating said sheet material to an elevated temperature; and
  - (d) allowing said sheet material and said substrate to cool,
  - 15 wherein said sheet material remains adhered to said substrate.
2. A method according to Claim 1, wherein said one or more thermosettable polymers comprise a polyester and a thermosettable component.
- 20 3. A method according to claim 2, wherein said thermosettable component comprises an epoxy resin and, optionally, a curative to polymerize said epoxy resin.
4. A method according to claim 1, wherein said polyolefin film is a  
25 polyethylene film.
5. A method for imparting (topographical) or protective features to a substrate comprising the steps of

55

5.0.0 421011  
7040 50000  
04-12-94  
156/278  
324.4

2029  
P, 6-19  
5

(a) providing a sheet material having a top surface and bottom surface, comprising two or more layers, comprising an upper layer and a lower layer, said upper layer being a polyester film with a cured epoxy/polyester (priming layer), wherein said (priming layer) forms the top surface of said sheet material, and said lower layer comprising a thermosettable melt-flowable composition comprising one or more thermosettable polymers;

(b) contacting said bottom surface of said sheet material with said substrate, leaving said top surface of said sheet material exposed;

10

(c) heating said sheet material to an elevated temperature; and

(d) allowing said sheet material and said substrate to cool, wherein said sheet material remains adhered to said substrate.

add a  
add B5